

**DIRECTORATE OF DISTANCE EDUCATION
NALSAR UNIVERSITY OF LAW, HYDERABAD
P.G.DIPLOMA IN PATENTS LAW**

2018-19 (Supplementary Exams)

**Paper II – Practical
(Exploitation of Patents – Drafting, Specification & Patent Writing)**

Time: 2 ½ hours.

TOTAL MARKS: 100

INSTRUCTIONS TO CANDIDATES

- 1. The question paper to be interpreted as given and no clarification can be sought from the invigilator.**
- 2. Attempt only one choice – either A or B**
- 3. Answers in illegible handwriting will not be taken into consideration.**

You are required to draft a complete specification containing; a.) Title of the Patent b.) Background of the Invention c.) Summary of the Invention d.) Claims e.) Abstract of the invention. (Do not write a detailed description or draw figures.)

The Claims in the patent draft carries 50 marks and remaining specification carries 50 marks.

Note:

The answer guidelines contain some points (non-exhaustive) that could be covered in the answer to the Paper.

[54] ANTI-EATING FACE MASK
[76] Inventor: Lucy L. Barmby, 9550 Jackson Rd.,
Sacramento, Calif. 95826
[21] Appl. No.: 134,557
[22] Filed: Mar. 27, 1980
[51] Int. Cl.³ A61F 5/56
[52] U.S. Cl. 128/136
[58] Field of Search 128/133, 136, 137
[56] References Cited


U.S. PATENT DOCUMENTS



853,025	5/1907	McCalmont	128/133
1,297,842	3/1919	Harlee	128/136
1,629,892	5/1927	Storms	128/136
2,276,612	3/1942	Ellis	128/136

3,189,073 6/1965 Todd 128/133
3,818,906 6/1974 Stubbs 128/136
Primary Examiner—Kyle L. Howell
Assistant Examiner—C. W. Shedd
Attorney, Agent, or Firm—Blair, Brown & Kreten

[57] ABSTRACT
An anti-eating face mask which includes a cup-shaped member conforming to the shape of the mouth and chin area of the user, together with a hoop member and straps detachably engageable with a user's head for mounting the cup-shaped member in overlying relationship with the user's mouth and chin area under the nose thereby preventing the ingestion of food by the user.

2 Claims, 3 Drawing Figures





ANTI-EATING FACE MASK

BACKGROUND OF THE INVENTION

Obesity is a basic problem with which many people today are confronted and, as clearly indicated by the variety of diets proposed to conquer overweight, the major contributing factor to overweight is the excessive consumption of food. The temptation to eat which leads one to eat excessively is ever present and the ready availability of attractively prepared, taste-tempting foods makes the temptation to eat and therefore to overeat virtually irresistible. Frequently, this temptation is so great that compulsive eating is not uncommon and many persons are virtually without the strength of will to resist overeating. The average person, therefore, does have a problem as to the over consumption of food but, even worse, when certain individuals are exposed to food constantly such as chefs, cooks, restaurant personnel or the like, it is a foregone conclusion that these individuals will consume far more food than is proper particularly when such food is usually readily available at no cost. Typical of such groups of individuals is the housewife who must frequently cook meals during the day which generally includes the preparation of such fattening foods such as pies, pastries, and the like. During the preparation of such meals not only is there the temptation to nibble on the food being prepared but it is generally necessary that the food be tasted during preparation thereby constantly stimulating the appetite and promoting the consumption of large quantities of food.

OBJECTS AND SUMMARY OF THE INVENTION

Accordingly, a primary object of this invention is to provide a new and novel device for preventing the consumption of food by an individual.

Another object of this invention is to provide a new and novel mask which is worn on the head of a user to prevent the consumption of food by the user and therefore an attendant overweight problem.

A further object of this invention is to provide a new and novel device which may be easily attached to the head of the user in a detachable manner for encompassing the mouth area of the user thereby preventing food from being ingested by the user.

Still another object of this invention is to provide a new and novel device which is worn on the head of the user for preventing the ingestion of food, which is simple and inexpensive in construction, which does not interfere with transmission of speech or breathing by the user and which may be locked in place on the user's head to prevent removal while at the same time permitting removal under emergency conditions.

A still further object of this invention is to provide a new and novel device for preventing the ingestion of food by a user which is useful in the prevention of overweight, which may be used in the medical profession to prevent food consumption during the period before an operation, which may be made in any suitable size and which may also be used to prevent the smoking of cigarettes and the like.

The objects stated above and other related objects are accomplished by the provision of a cup-shaped member conforming generally to the shape of the mouth and chin area of a user's face below the nose. The cup-shaped member is provided with mounting means engageable with the head of a user which permits the

member to be positioned in overlying relationship with the mouth and chin area of the user's face so that ingestion of food by the user is prevented.

Other objects and advantages will become apparent when viewed in the light of the following description taken in connection with the accompanying drawing.

BRIEF DESCRIPTION OF THE DRAWING

FIG. 1 is a profile view of a user's head showing the anti-eating face mask of the invention in an installed position;

FIG. 2 is an enlarged front view of the face mask of FIG. 1; and

FIG. 3 is an enlarged sectional view taken substantially along 3—3 of FIG. 2 in the direction of the arrows.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings there is shown the anti-eating face mask of the invention which is designated generally by the letter M. The face mask M is shown in the installed position on the face of a user's head in FIG. 1 and includes a cup-shaped member 16 of rigid material such as wire or the like which conforms generally to the mouth and chin area of a user's face below the nose. In the illustrated embodiment, the cup-shaped member 16 is formed from a plurality of wires 17 which are arranged as shown best in FIG. 2 in a unitary construction to define openings 18 therebetween. The openings 18 are of a size to permit speech plus, at the same time, prevent the ingress of food into the mouth of the user.

Means engageable with the user's head are provided on the mask M for detachably mounting the cup-shaped member 16 in overlying relationship with the user's mouth and chin area. More specifically, the cup-shaped member 16 is secured by means of rods or wires 21—23 to a hoop member 24 which is arranged to encircle the user's head extending around the top of the head, the side areas of the face and under the chin. Rods 21, 22 extend outwardly on opposite sides of the cup-shaped member 16 and are attached at the outer ends to the hoop member 24, rod 23 extending between the bottom of the cup-shaped member 16 to the lower portion of the hoop member 24, as shown in FIG. 1, thereby providing a rigid construction comprising the hoop member 24 and the cup-shaped member 16.

The mounting means of the invention also includes a flexible strap 26 having end portions 26a, 26b attached to the hoop member 24. The mounting means also include a strap member 27 connected at one end 27a to the top of the hoop member 24 and at the other end 27b to the flexible strap 26 intermediate the ends 26a, 26b. In the illustrated embodiment, both straps 26, 27 are preferably formed from leather. The end 26b of flexible strap 26 may be attached in any suitable manner permanently to the hoop member 24 as shown in FIG. 2 and the other end portion 26a of the strap 26 is preferably releasably attached to the hoop member 24 as shown best in FIG. 3.

As shown in FIG. 3, the end portion 26a of strap 26 is provided with a staple 31 suitably secured thereto and a slotted aperture 32, longitudinally spaced from the staple 31, for accommodating the staple 31. Thus, the strap end portion 26a is arranged to be formed into a loop around the hoop member 24 and the staple 31

3

inserted into the slotted aperture 32 so as to extend outwardly from the strap end portion 26a. In the preferred embodiment, locking means are included with the mounting means of the invention which includes any conventional lock 33 of the type using a key which lock is engageable with the staple 31 in the position shown in FIG. 3 so as to lock the end portion 26a of the strap 26 on the hoop 24 preventing its removal. However, under emergency conditions, the strap 26 may be cut and the face mask M of the invention removed.

In the illustrated embodiment, the strap 26 is shown extending over the user's ear but it should be understood that, if desired, the strap 26 may be positioned below the user's ear as shown in broken lines and as indicated by the reference numeral 26'. The strap member 27 is extended in length accordingly to connect the end 27b with the strap 26'.

Having thus described the preferred embodiment of the invention it should be understood that numerous structural modifications and adaptations may be resorted to without departing from the spirit of the invention.

What is claimed is:

1. A face mask for preventing the introduction of substances into the mouth of the wearer comprising in combination;

a cup shaped member conforming generally to the shape of the mouth and chin area of the wearer's face below the nose, said cup shaped member formed of rigid material with openings to allow breathing therethrough,

4

means for mounting said cup shaped member over the mouth including plural straps extending from said cup over the head of the wearer,

one of said straps provided with a means for separation to allow for placement and removal of said face mask, and a lock at said separation means to prevent removal of said face mask, said mounting means further including a hoop member of rigid material adapted to extend over the user's head and chin and a flexible strap having end portions connected to said hoop member for extending around the back of the user's head and a strap member adapted to extend over the top of the user's head, said strap member being connected at opposite ends to said hoop member and to said strap intermediate the ends of said strap, said separation means including a staple adjacent one end portion of said strap, and an aperture in said strap one end portion in longitudinally spaced relationship with said staple, said strap one end portion arranged to be looped around said hoop member for insertion of said staple in said aperture and said lock engageable with said staple extending through said aperture for locking said strap one end portion to said hoop member, wherein said hoop member is attached to said cup shaped member by plural rods extending therebetween, two of said rods attached to opposed sides of said cup shaped member, a third said rod attached to a lowermost portion of said hoop member.

2. A face mask in accordance with claim 1 wherein said cup-shaped member comprises a screen formed of a plurality of wires, said wires in said screen defining said openings therebetween.

* * * * *



(12) **United States Patent**
Daugherty

(10) **Patent No.:** **US 7,484,328 B1**
(45) **Date of Patent:** **Feb. 3, 2009**

(54) **FINGER MOUNTED INSECT DISSUASION
DEVICE AND METHOD OF USE**

(76) Inventor: **John Richard Daugherty**, 1647 N.
Woodhollow Way, Flagstaff, AZ (US)
86004

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 122 days.

(21) Appl. No.: **11/080,023**

(22) Filed: **Mar. 15, 2005**

Related U.S. Application Data

(63) Continuation-in-part of application No. 10/839,590,
filed on May 5, 2004, now abandoned.

(51) **Int. Cl.**
A01M 3/02 (2006.01)
A01M 3/00 (2006.01)

(52) **U.S. Cl.** **43/137; 43/134**
(58) **Field of Classification Search** **43/137,**
43/134

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

36,652 A	10/1862	Jacobs	
97,161 A *	11/1869	Buttles	43/134
160,606 A *	3/1875	Marsh	43/134
542,464 A *	7/1895	Chase	43/137
599,404 A *	2/1898	Robertson	43/134
609,160 A *	8/1898	McWithey	43/134
648,336 A *	4/1900	Bellamy	273/317.2
974,887 A	11/1910	Huddle	
1,099,342 A *	6/1914	Copenhaver	43/137
1,206,976 A	12/1916	Barth	
1,354,775 A *	10/1920	Moore	43/137
1,412,312 A *	4/1922	Little	43/137
1,479,046 A *	1/1924	Herbert	43/137
1,500,442 A *	7/1924	Cooper	43/137
1,639,559 A *	8/1927	Gatch	43/137

1,650,548 A *	11/1927	Sullivan	43/137
1,656,969 A *	1/1928	Adolph	43/137
1,660,011 A *	2/1928	Linding	43/137
1,662,264 A *	3/1928	Henderson	43/137
1,763,205 A *	6/1930	Winbigler	273/317.2
1,820,360 A *	8/1931	Meggitt	43/137
1,861,688 A *	6/1932	Crawford	43/137
1,942,252 A *	1/1934	Martin	43/137
1,967,384 A *	7/1934	Urbanek	43/137

(Continued)

FOREIGN PATENT DOCUMENTS

DE 29712704 U1 * 11/1997


(Continued)

Primary Examiner—Darren W Ark
(74) *Attorney, Agent, or Firm*—John R. Daugherty

(57) **ABSTRACT**

An insect dissuasion method that incorporates a miniature fly swatter adapted to be fixed onto an end of a human finger. An insect can be discouraged by simply flexing, slowly encroaching upon and then “flicking” the finger with the attached device to strike the insect. Devices of the present invention are designed to be removably attached to a finger by a ring-like structure. The ring-like structure is tailored to slip onto and engage a finger in various positions and remain attached to the finger when the finger is flicked. Joined to the ring-like structure is an extension shaft that terminates in an insect engagement head. The length and/or cross-sectional profile of the extension shaft can be altered as well as the shape of the head portion or ring-like structure.

3 Claims, 13 Drawing Sheets



US 7,484,328 B1

Page 2

U.S. PATENT DOCUMENTS


2,015,092 A * 9/1935 Turnquist 43/137
 2,022,615 A * 11/1935 Bennett et al. 43/137
 2,023,209 A * 12/1935 Platt 43/137
 2,083,727 A * 6/1937 Matteson 43/137
 2,096,940 A * 10/1937 Platt 43/137
 2,122,901 A * 7/1938 Urbanek 43/137
 2,126,311 A * 8/1938 Cowen 43/137
 2,136,233 A * 11/1938 Brownson 43/137
 2,157,106 A * 5/1939 Baker 43/137
 2,189,565 A * 2/1940 Jones 43/137
 2,199,044 A * 4/1940 Creary 43/137
 2,207,963 A * 7/1940 White 43/137
 2,209,260 A * 7/1940 Cummings 43/137
 2,260,106 A * 10/1941 Miller 43/137
 2,268,272 A * 12/1941 White 43/137
 2,394,267 A * 2/1946 Sorkind 43/137
 2,410,957 A * 11/1946 Briones 43/137
 2,485,822 A * 10/1949 Goldrich 43/137
 2,496,415 A * 2/1950 Sharpe 43/137
 2,545,215 A * 3/1951 Sharpe 43/137
 2,604,723 A * 7/1952 Bennett 43/137
 2,618,882 A * 11/1952 Martin 43/137
 2,624,149 A * 1/1953 Atkinson 43/137
 2,651,878 A * 9/1953 Webbeking 43/137
 2,697,895 A * 12/1954 King 43/137
 2,712,708 A * 7/1955 Hale 43/137
 2,735,217 A * 2/1956 Hufnagel 43/137
 2,806,320 A * 9/1957 Griffith 43/137
 2,891,347 A * 6/1959 Swint 43/137
 2,934,851 A * 5/1960 Grish 43/137
 2,963,816 A * 12/1960 De Miller 43/137
 3,005,441 A * 10/1961 Glasscock
 3,402,984 A * 9/1968 Zazzara
 3,412,501 A * 11/1968 Rosen 43/137
 3,596,964 A * 8/1971 Zazzara
 3,648,402 A * 3/1972 Siggers 43/137
 4,095,793 A * 6/1978 Ray
 4,120,114 A * 10/1978 Little et al. 43/137
 4,120,115 A * 10/1978 Mushkin 43/137
 4,127,338 A * 11/1978 Laybourne
 4,195,615 A * 4/1980 Belokin 43/135
 4,291,874 A * 9/1981 Peterson 273/449
 4,442,837 A * 4/1984 Keatley 43/134
 4,502,243 A * 3/1985 Spindler 43/137
 4,593,489 A * 6/1986 Gott et al. 43/137
 4,674,227 A * 6/1987 Maier 43/137
 4,694,605 A * 9/1987 Garcia et al. 43/137
 4,733,867 A * 3/1988 Kemp et al.
 4,738,556 A * 4/1988 Brown
 4,765,208 A * 8/1988 Sakosky
 4,774,786 A * 10/1988 Zaremba



4,793,094 A * 12/1988 Weaver 43/137
 4,797,974 A * 1/1989 Smith, Jr.
 4,872,679 A * 10/1989 Bohaski et al.
 4,910,909 A * 3/1990 Johnson et al.
 D311,050 S * 10/1990 Lisitza
 5,027,549 A * 7/1991 Person 43/134
 5,052,967 A * 10/1991 Slatter et al.
 5,086,612 A * 2/1992 Anderson
 5,110,127 A * 5/1992 Potter
 5,242,164 A * 9/1993 Nicoll 273/317.1
 D349,940 S * 8/1994 Blaisdell D22/124
 5,391,010 A * 2/1995 Gorbunov
 5,405,206 A * 4/1995 Bedol
 D358,446 S * 5/1995 Cooper D22/124
 5,492,046 A * 2/1996 Jimenez
 5,586,407 A * 12/1996 Raymond
 5,671,925 A * 9/1997 Gonzalez
 5,709,385 A * 1/1998 Fitzpatrick et al.
 5,722,575 A * 3/1998 Smith
 5,794,377 A * 8/1998 Kensok et al. 43/134
 5,868,509 A * 2/1999 Crutcher
 5,881,745 A * 3/1999 Landis 132/323
 5,885,018 A * 3/1999 Sato
 D407,790 S * 4/1999 Miceli
 5,971,642 A * 10/1999 O'Mara et al.
 D418,494 S * 1/2000 Robb
 6,065,480 A * 5/2000 Mader 132/323
 6,161,328 A * 12/2000 Sing 43/137
 6,185,862 B1 * 2/2001 Nelson 43/137
 6,247,992 B1 * 6/2001 Higgins, III
 6,279,262 B1 * 8/2001 Walkemeyer 43/137
 6,367,797 B1 * 4/2002 McKenna-Cress et al.
 D464,103 S * 10/2002 Jensen
 6,527,464 B2 * 3/2003 Lee
 6,626,598 B2 * 9/2003 Schneider
 6,631,723 B1 * 10/2003 Mullin
 6,651,379 B1 * 11/2003 Nelson
 6,669,388 B1 * 12/2003 Short
 6,851,218 B1 * 2/2005 Conte 43/137
 6,957,510 B1 * 10/2005 Kominkiewicz 43/137
 2001/0007392 A1 * 7/2001 Sugarman
 2003/0131524 A1 * 7/2003 Brown

FOREIGN PATENT DOCUMENTS

DE 10320040 A1 * 12/2004
 EP 461397 A1 * 12/1991
 GB 1596043 A * 8/1981
 GB 2124880 A * 2/1984
 GB 2248166 A * 4/1992
 WO WO 02/37959 A1 * 5/2002

* cited by examiner









Fig. 6A




Fig. 6B




Fig. 6C




Fig. 6D




Fig. 7




Fig 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13 A




Fig. 13 B




Fig. 14




Fig. 15A




Fig. 15B




Fig. 15C




Fig. 15D




Fig. 15E




Fig. 15F




Fig. 15G




Fig. 15H




Fig. 16A




Fig. 16B




Fig. 16C




Fig. 16D




Fig. 16E




Fig. 16F




Fig. 16 G




Fig. 16 H




Fig. 16 J




Fig. 17




Fig. 18



Fig. 19







Fig. 20





1

FINGER MOUNTED INSECT DISSUASION DEVICE AND METHOD OF USE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation in part and claims the benefit of U.S. application Ser. No. 10/839,590, filed May 5, 2004, now abandoned the contents of which are incorporated herein by this reference.

FIELD OF THE INVENTION

Devices and methods of the present invention relate to mechanical insect dissuasion devices and in particular to finger mounted fly swatters.

BACKGROUND OF THE INVENTION

During outdoor activities one is often annoyed or distracted by an insect. For example during static outdoor activities such as sun-tanning or reading, a single fly will often persist in annoyance despite repeated attempts to "discourage" the insect. Such an insect persistently fly's and lands on one's arm or leg for example. Conventional fly-swatters are cumbersome and due to hygiene concerns, are not well suited for "swatting" one's self. Often one uses their hand, book or other object to brush away and discourage the insect. Such attempts are most often ineffective since the insect simply fly's away and returns to a different location.

The present invention relates to finger-mounted devices and methods of using such devices to dissuade insects. There are several prior references disclosing various finger-mounted devices. Examples of these finger-mounted devices include toothbrushes, dental flossing devices, pens and writing instruments, string instrument picks, computer touch screen styluses and surgical instruments. None of these references disclose or suggest the use of such devices for the dissuasion of insects. In addition, the use of these devices in the manner presently claimed by the applicant would present hygiene concerns or destroy the intended use of the devices. U.S. Pat. No. 1,763,205 (Winbigler) and U.S. Pat. No. 648,336 (Bellamy) disclose finger-mounted game devices specifically used to propel miniature golf balls and are also devoid of any teaching or suggestion relating to the dissuasion of insects.

SUMMARY OF THE INVENTION

The present invention is an insect dissuasion device that resembles a miniature fly swatter adapted to be fixed onto an end of a human finger. When a device of the present invention is attached for example onto an index finger, normal activities such as holding a book or a drink container are unimpeded. An insect can be spontaneously discouraged by simply flexing, slowly encroaching upon and then "flicking" the finger and the attached device of the present invention. Due to the small size of the "finger fly swatter" most insects do not react to its presence and are caught off-guard by the rapid flicking motion. Most insects are easily struck and swept away from one's body by the device of the present invention, resulting in permanent removal of the particular insect. The small inconspicuous size of the finger fly swatter allows for easy cleaning if needed. The device of the present invention is so effective in the dissuasion of insects that one often welcomes the presence of an insect so that it may be discouraged. The dissuasion of a particularly energetic insect often becomes a challenging sport.

2

In a preferred embodiment, a device of the present invention is removably attached to a finger by a ring-like structure. The ring-like structure is tailored to slip onto and engage a finger in various positions and remain attached to the finger when the finger is flicked. Joined to the ring-like structure is an extension shaft that terminates in an insect engagement head portion. The length and/or cross-sectional profile of the extension shaft can be altered as well as the shape of the head portion or ring-like structure.

BRIEF DESCRIPTION OF DRAWINGS

Shown in FIG. 1 is an isometric view of an insect dissuasion device resembling a miniature "fly swatter" according to a preferred embodiment of the present invention.

FIG. 2 is an isometric view of a device of the present invention releasably attached to an index finger.

FIG. 3 is an isometric view of a device of the present invention releasably attached to a second finger.

Shown in front view FIG. 4 is a device of the present invention releasably attached to a distal phalanx bone of a human finger.

Shown in front view FIG. 5, a device of the present invention releasably attached to a middle phalanx bone of a human finger.

FIGS. 6A through 6D show respectively, top views of a device of the present invention positioned onto an outside, a top, an inside and a bottom surface of a human finger.

Shown in FIG. 7 is an isometric view of a preferred embodiment of an insect dissuasion device of the present invention. Shown is a finger engagement portion, an extension shaft and a head engagement portion.

FIG. 8 is an isometric view of a device of the present invention having a slit in the finger engagement portion.

FIG. 9 is an isometric view of an alternate, sock or finger-cot configuration of a finger engagement portion of the present invention.

FIG. 10 is a side view of a device of the present invention showing end regions, coupling points and the length of an extension shaft of the present invention.

FIG. 11 is a side view of a device of the present invention showing a head portion that is positioned distally of the finger distal end.

FIG. 12 is a side view of an alternate embodiment of the present invention having a head portion that is "integral" with the extension shaft.

FIGS. 13A and 13B show side views of a device of the present invention. Depicted is an optional feature allowing length adjustment of an extension shaft.

FIG. 14 is a side view of a device of the present invention defining a cross-sectional viewing plane of an extension shaft.

FIGS. 15A through 15H are examples of various extension shaft cross-sectional profiles according to the present invention.

FIGS. 16A through 16J are front or isometric view examples of various head portions according to the present invention (16I excluded for clarity).

FIG. 17 is a top view of a finger with an attached device of the present invention. Shown is a finger longitudinal axis having an angular offset to the extension shaft longitudinal axis.

FIG. 18 is a partial top view of an extension shaft of the present invention displaying a printed logo.

FIG. 19 is an isometric view of a wire-formed device of the present invention.

3

FIG. 20 is a solid model perspective view of a preferred embodiment of the present invention.

FIG. 21 is a perspective view of an extension shaft portion showing relations between cross-sectional perimeter lengths and overall shaft lengths.

FIG. 22 is a side view of a device of the present invention defining angular relations between three longitudinal axis.

DETAILED DESCRIPTION OF DRAWINGS

The bones of the fingers (and toes) are known as phalanges (singular: phalanx). Each finger has three phalanges, with the exception of the thumb, which has only two. The phalanges are referred to by their position with respect to the body when the hand is extended. The bones at the ends of the fingers, because they are the most distant from the body, are the distal phalanges. The next are the middle phalanges (which the thumb does not have). Those articulating with the metacarpals of the hand are the proximal phalanges.

Shown in FIG. 1 is an insect dissuasion device 20 resembling a miniature "fly swatter" according to a preferred embodiment of the present invention. Shown is an isometric rendering of a human hand 25 having an index or first finger 30a in a "pre-flicked" or curled state. Releasably attached to the index finger 30a is an insect dissuasion device 20 of the present invention. From this position, the index finger and the attached device of the present invention can be "flicked" to strike an insect or other object. The term "flicked" as used herein is defined as a rapid transition of a finger from a contracted or curled state to an approximately linear extended state. The concept of "flicked" is illustrated in FIG. 1. The index finger is initially in a curled state 30a and is then rapidly moved 35 to an approximately linear extended state 30b. When the finger is flicked the attached device 20 of the present invention is used to contact or strike an insect 40 or other object. As an alternate to a finger flicking motion, the device of the present invention can be used with a simple striking motion wherein the finger is not initially curled as shown in FIG. 1.

The following definition excerpt from *Merriam-Websters Collegiate Dictionary*, 11th Edition, comport with the usage of "strike":

STRIKE

Main Entry: 1 strike

2a: to aim and usually deliver a blow, stroke, or thrust (as with the hand, a weapon, or a tool)

3: to come into contact forcefully *two ships struck in mid channel*

1a: to strike at: HIT b: to drive or remove by or as if by a blow c: to attack or seize with a sharp blow (as of fangs or claws) "struck by a snake"

d: INFLICT "strike a blow"

9a(1): to bring into forceful contact

There are several finger locations and orientations suitable for use with devices of the present invention. For example as shown in isometric FIG. 2, a device of the present invention 20 can be releasably attached to an index finger 30. In an alternate position shown in isometric FIG. 3, a device of the present invention 20 can be releasably attached to a second finger 45. Other digits of a hand that are suitable for attaching a device of the present invention include a third finger 46, a fourth finger 47 and a thumb 48.

Devices of the present invention can also be releasably attached to different phalanges of a finger. For example as shown in front view FIG. 4, a device of the present invention 20 can be releasably attached to a distal phalanx 50. In an

4

alternate position shown in front view FIG. 5, a device of the present invention 20 can be releasably attached to a middle phalanx 55. Devices of the present invention can also be releasably attached to proximal phalanges. Although the effectiveness of the flicking motion is compromised, the attachment to a proximal phalanx provides a convenient means for "storing" a device of the present invention. When attached to a proximal phalanx, normal use of the hand is less impaired and a device of the present invention can be readily repositioned to a more effective flicking position.

Devices of the present invention can also be releasably attached onto and oriented about different angular positions of a finger. For example as shown in top view FIG. 6A, a device of the present invention 20 can be oriented about the outside or nail surface of a finger. Shown is a finger 30, a device of the present invention 20 having a finger engagement portion 60, an extension shaft 65 and a striking head portion 70. When oriented about the outside of a finger, the extension shaft 65 is adjacent to the outside or nail surface of a finger.

Alternately, a device of the present invention can be rotated about 90° from the position shown in FIG. 6A, so that an extension shaft 65 is adjacent the top side of a finger. This orientation of a device of the present invention is depicted in top view FIG. 6B showing a device on the top of a finger in an orientation similar to that shown in FIG. 1. Devices of the present invention can also be positioned so that an extension shaft 65 is adjacent an inside surface of a finger. Shown in top view FIG. 6C is a device of the present invention 20 oriented so that an extension shaft 65 is adjacent the inside surface of a finger. In this orientation a device of the present invention is rotated approximately 180° from the position shown in FIG. 6A, so that an extension shaft 65 is adjacent the inside surface of a finger.

Devices of the present invention can also be positioned so that an extension shaft 65 is adjacent a bottom surface of a finger. Shown in top view FIG. 6D is a device of the present invention 20 oriented so that an extension shaft 65 is adjacent the bottom surface of a finger. In this orientation a device of the present invention is rotated approximately 180° from the position shown in FIG. 6B, so that an extension shaft 65 is adjacent the bottom surface of a finger.

Shown in FIG. 7 is a preferred embodiment of an insect dissuasion device 20 that resembles a miniature "fly swatter" adapted to be fixed onto an end of a human finger. A device 20 of the present invention preferably has a finger engagement portion 60, coupled to an extension shaft 65 that terminates into a head portion 70. In one embodiment, the finger engagement portion 60 can be configured to resemble and function like a common finger ring. In such a configuration, the finger engagement portion 60 is dimensioned to slip-fit onto and remain attached to a human finger. When desired, the ring-like structure can be "worked-loose" and removed, thereby being "releasably attached" to the finger. The finger engagement portion can be formed of a resilient, compliant material or be semi-rigid. The inside or finger-contacting surface of a finger engagement portion can optionally incorporate friction or retention enhancing features. Such features include but are not limited to high-friction coatings, pressure point protrusions or "fish scale-like" angled flaps that resist removal of a finger.

Optionally, a ring-like finger engagement portion 60 can incorporate a slit 75 as shown in isometric view FIG. 8. By incorporating a slit 75, a more rigid material such as a rigid plastic or ductile metal can be used to form the finger engagement portion 60. In this embodiment the finger engagement portion can be deformed by a user to accommodate the particular dimensions of a specific finger. As an alternate to a slit,

5

a finger engagement portion of the present invention can also incorporate a circumferential "over-lap" (commonly found on finger rings) to provide user selected sizing.

Finger engagement portions **60** of the present invention can also utilize a "finger-cot" or slip-on cup configuration **80** as shown in FIG. **9**. A cup **80** can be formed from a resilient, compliant material or be semi-rigid and sized to fit a specific range of finger dimensions.

Shown in FIG. **10** is a side view of a device of the present invention **20** having a finger engagement portion **60**, an extension shaft **65** and a head portion **70**. The extension shaft **65** has a first end region **85** coupled to the finger engagement portion **60** that defines a first coupling point **95**. The extension shaft **65** has a second end region **90** coupled to the head portion **70** defining a second coupling point **100**. The extension shaft has a length **105** defined as the approximate distance between the first coupling point **95** and second coupling point **100**.

Shown in FIG. **11** is a side view of a device of the present invention **20** with a finger engagement portion **60** releasably attached to a distal phalanx **50** of an index finger **30**. The finger **30** has a distal end **110** and the device head portion **70** is shown in a position that is distal to the finger distal end **110**. The device head portion may also be juxtaposed to, adjacent to or proximal to the distal end **110** of a finger. The device head portion may also overlay or be in contact with the finger nail or any other portion of the finger.

An alternate embodiment of the present invention is shown in FIG. **12**. Shown is a side view of a device of the present invention **20** having an engagement head portion **70** that is integral to an extension shaft **65**. An "engagement head" is defined as any structure coupled to or integral to a finger engagement portion or extension shaft that has the intended purpose of striking an insect or other object.

In an alternate preferred embodiment, devices of the present invention can incorporate a slip or adjustable fit feature at the first coupling point between a finger engagement portion **60** and an extension shaft **65**. This slip-fit feature allows a user to interchange various shafts or to adjust the effective length **105** of the extension shaft. Shown in side view FIG. **13A** is a device of the present invention **20** having a head portion **70**, an extension shaft **65** and a finger engagement portion **60**. The coupling **95** between the extension shaft **65** and the finger engagement portion **60** allows the extension shaft to be adjusted to length **105a**. Shown in side view FIG. **13B** is a device of the present invention **20** wherein the extension shaft has been adjusted to a shorter length **105b**. The first coupling point **95** has a slip fit feature that allows positional adjustment between the finger engagement portion and the extension shaft. Devices of the present invention can have extension shaft lengths **105** ranging from about 5 mm (0.2") to about 130 mm (5.2") or greater. A preferred range of extension shaft lengths **105** is from about 20 mm (0.8") to about 80 mm (3.2"). Extension shaft lengths of the present invention can be about 5 mm (0.2"), about 10 mm (0.4"), about 15 mm (0.6"), about 20 mm (0.8"), about 25 mm (1"), about 30 mm (1.2"), about 35 mm (1.4"), about 40 mm (1.6"), about 45 mm (1.8"), about 50 mm (2"), about 60 mm (2.4"), about 70 mm (2.8"), about 80 mm (3.2"), about 90 mm (3.6"), about 100 mm (4"), about 110 mm (4.4"), about 120 mm (4.8"), about 130 mm (5.2") or greater.

As shown in side view FIGS. **13A** and **13B** the proximal end **115** of the extension shaft is retracted (FIG. **13A**) or extended (FIG. **13B**) relative to the finger engagement portion **60**. The slip-fit feature, allowing shaft interchangeability and adjustability, can be a properly sized through hole in the finger engagement portion that provides adequate friction between the through hole and the extension shaft. Deform-

6

able pinch points, adhesives, snap locks, set screws, wedges or any suitable means can be incorporated into the coupling point **95** to allow interchangeability, adjustment and retention of an extension shaft.

Also shown in FIG. **13B** is a finger engagement portion **60** having a longitudinal length **120**. Embodiments of the present invention can have finger engagement longitudinal lengths **120** ranging from about 1 mm (0.04") to about 20 mm (0.8"). A preferred range of finger engagement longitudinal lengths **120** is from about 3 mm (0.1") to about 15 mm (0.6"). A more preferred range of finger engagement longitudinal lengths **120** is from about 5 mm (0.2") to about 10 mm (0.4").

Extension shafts of the present invention can have various shapes and cross-sectional profiles. Shown in FIG. **14** is a side view of a device of the present invention **20** having an extension shaft **65** with a longitudinal axis **125**. Cross-sectional plane **15** defines a viewing plane orthogonal to the longitudinal axis **125** of the extension shaft **65**. FIGS. **15A** through **15H** are example cross-sectional views of extension shafts as viewed along a shaft longitudinal axis.

Shown in FIG. **15A** is an extension shaft **65a** that has a round or circular profile. Extension shafts can have an oval shaped, hollow tube shaped or partial tube shaped profile.

Shown in FIG. **15B** is an extension shaft **65b** having a square profile. Extension shafts can have a square hollow tube shaped or partial tube shaped profile.

Shown in FIG. **15C** is an extension shaft **65c** having a rectangular profile and FIG. **15D** depicts an extension shaft **65d** having a "tee" shaped profile.

Shown in FIG. **15E** is an extension shaft **65e** having a "L" shaped profile and FIG. **15F** depicts an extension shaft **65f** having a channel or "C" shaped profile.

Shown in FIG. **15G** is an extension shaft **65g** having a triangular shaped profile and FIG. **15H** depicts an extension shaft **65h** having a "cross" shaped profile. Other possible cross-sectional profiles include polygons or irregular shapes.

A preferred embodiment of the present invention incorporates a slip or adjustable fit feature at the first coupling point between a finger engagement portion and an extension shaft. This slip-fit feature, generally depicted in FIGS. **13A** and **13B**, allows a user to interchange various shafts and to adjust or vary the effective length of the extension shaft. The example profiles shown in FIGS. **15A** through **15H** can be adapted to slip fit into a matching hole in a finger engagement portion. Specific profiles can allow various adjustments of the angular relation between a finger engagement portion and an extension shaft or between an extension shaft and a head portion. For example a round profile allows infinite angular adjustment (or rotation along the extension shaft longitudinal axis) between the two components. A regular triangular shaped profile, as shown in FIG. **15G**, allows three angular positions, while a square profile (FIG. **15B**) or a cross profile (FIG. **15H**) allow four angular orientations.

Devices of the present invention can have head portions of various configurations examples of which are shown in side view FIGS. **16A** through **16J** (**16I** excluded for clarity). Shown in FIG. **16A** is a head portion **70a** having a paddle shape. Shown in FIG. **16B** is a paddle shaped head portion **70b** having a centerline axis **120** that is offset from the extension shaft longitudinal axis **125**.

Shown in FIG. **16C** is a paddle shaped head portion **70c** having holes, spikes or dimples **130**. Shown in FIG. **16D** is a paddle shaped head portion **70d** having a tapered or pointed shaped tip **135**.

The following definition excerpt from *Merram-Webster's Collegiate Dictionary*, 11'th Edition, comport with the usage of "paddle":

PADDLE

Main Entry: 2 paddle

1a: a usually wooden implement that has a long handle and a broad flattened blade and that is used to propel and steer a small craft (as a canoe) b: an implement often with a short handle and a broad flat blade that is used for stirring, mixing, or hitting; especially: one used to hit a ball in any of various games (as table tennis)

2b: any of the broad blades attached to a shaft (as in an ice cream machine) and used for stirring

A paddle head portion can be further defined as a three dimensional shape having a length, a height and a thickness. The length and height define a striking surface or plane that is perpendicular to a "striking axis" that is parallel to the finger flicking axis as shown in FIG. 1, item 35. The length is at least equal to the height. The thickness is less than about 1/3 of the smaller of the length or height. The striking surface may have through holes or may have a concave or convex profile. The paddle head portion is joined to an elongate shaft or handle.

Shown in FIG. 16E is a "whip" shaped head portion 70E having a thin elongate portion 140 terminating in a ball 145. The ball 145 can incorporate spikes and can be of any bulbous shape. Other whip-like configurations can include, but are not limited to, whips not having a bulbous shape near the end as generally depicted in FIG. 12.

Shown in FIG. 16F is a "whip" shaped head portion 70F having a thin elongate portion 140 terminating in a spike 150. Multiple spikes 150 can be incorporated into the terminal end of the elongate structure 140.

A whip-like configuration can have various cross-sectional profiles and have a length equivalent to the "extension shaft" lengths previously defined.

The following definition excerpt from *Merriam-Websters Collegiate Dictionary*, 11'th Edition, comport with the usage of "whip":

WHIP

Main Entry: 2 whip

1: an instrument consisting usually of a handle and lash forming a flexible rod that is used for whipping

7: the quality of resembling a whip especially in being flexible 8: WHIP ANTENNA

Rod shaped head portions can also be incorporated into the present invention. A "rod" shaped head is similar to a whip except the rod is generally stiffer and less flexible than a whip. Such rod shapes can have various cross-sectional profiles, shown for example in FIGS. 15A through 15H. A rod-like configuration can have a length equivalent to the "extension shaft" lengths previously defined.

The following definition excerpt from *Merriam-Webster's Collegiate Dictionary*, 11'th Edition, comport with the usage of "rod":

ROD

Main Entry: rod

1a(1): a straight slender stick growing on or cut from a tree or bush b(1): a slender bar (as of wood or metal)

Shown in FIG. 16G is a "rake" shaped head portion 70G having a thin elongate portion 140 terminating in a rake configuration 170. The rake configuration includes at least two elongate fingers and is similar in shape to a common "leaf rake" or fork.

Shown in FIG. 16H is a "human hand" shaped head portion 70H having a thin elongate portion 140 terminating in a human hand configuration 175. The human hand can have an open, slapping configuration as shown or have a "closed fist" configuration.

Shown in FIG. 16J is a "butterfly net" shaped head portion 70J having a thin elongate portion 140 terminating in a butterfly net configuration 180.

Other striking head configurations adaptable to the present invention can include, but are not limited to shapes such as blocks, coiled springs, baseball bats, hockey sticks, tennis rackets, golf clubs, leg portions with a kicking boot, boxing gloves, swords, animal shapes such as cobra snakes, sharks, predator birds and "alien monsters".

Shown in FIG. 17 is a device of the present invention 20 attached to a finger 30 having a distal phalanx longitudinal axis 155. Also shown is an extension shaft longitudinal axis 125. An optional or adjustable angle 160 can be incorporated into devices of the present invention allowing the distal phalanx longitudinal axis 155 to have an angular offset to the extension shaft longitudinal axis 125. Other alternate embodiments of the present invention include a finger-mounted fly swatter having double or two-ring-like finger engagement portions. The two ring-like or other structures can be releasably attached to a single finger bone segment or onto two different bone segments. Such devices can include the incorporation of a pivot mechanism at one or more of the coupling points between a finger engagement portion and an extension shaft. Devices of the present invention can also incorporate a deformable extension shaft so that a user can form and set arcs, twists or other shapes onto an extension shaft. As shown in FIG. 18, devices of the present invention can be labeled or patterned with logos, trademarks, trade-names or other visual indicators. Shown in partial top view FIG. 18 is an example logo 165 printed onto an extension shaft 65.

Shown in FIG. 19 is an alternate embodiment of an insect dissuasion device according to the present invention. Shown in FIG. 19 is a wire-formed device of the present invention 21 having a finger engagement portion 60, coupled to an extension shaft 65 that terminates into a head portion 70.

Shown in FIG. 20 is a preferred embodiment of the present invention. Shown is a solid model of a device 200 of the present invention having a finger engagement portion 60, coupled to an extension shaft 65 that terminates into a striking head portion 70. The coupling point between the extension shaft 65 and the finger engagement portion 60 incorporates a tight slip fit feature that allows interchangeability of various extension shafts with different striking head configurations. The slip fit feature also allows adjustability of the effective length of the extension shaft. The longitudinal axis of the extension shaft has an angular offset of about 30° from the longitudinal axis of a human distal phalanx as shown in FIG. 17.

Shown in FIG. 21 is a general perspective view of a portion of an extension shaft 140 according to the present invention. As shown the shaft 140 has various cross-sectional perimeters 210A, 210B that are perpendicular to the shaft longitudinal axis 125 as viewed along the shaft longitudinal axis 125. To be considered a "shaft" within the scope of the present invention, two cross-sectional perimeters, separated by at least about 10 mm (0.4"), each must have an overall perimeter length that is substantially less than the overall length 205 of the shaft.

The following definition excerpt from *Merriam-Webster's Collegiate Dictionary*, 11'th Edition, comport with the usage of "shaft":

Main Entry: 1 shaft

1a (1): the long handle of a spear or similar weapon (2): SPEAR, LANCE: POLE; c (1): an arrow especially for a longbow (2): the body or stem of an arrow extending from the nock to the head 3: something suggestive of the

9

shaft of a spear or arrow especially in long slender cylindrical form: as a: the trunk of a tree b: the cylindrical pillar between the capital and the base c: the handle of a tool or instrument (as a golf club) e: the stem or central axis of a feather f: the upright member of a cross especially below the arms g: the cylindrical part of a long bone between the enlarged ends h: a small architectural column (as at each side of a doorway) i: a column, obelisk, or other spire-shaped or columnar monument

Shown in FIG. 22 is a side view of a device 20 of the present invention showing preferred angular relations between three longitudinal axis. Shown is a finger engagement portion 60, attached to an extension shaft 65 that terminates into a striking portion 70. The finger engagement portion 60 has a longitudinal axis 155 that is coincident with the distal phalanx longitudinal axis (as defined in FIG. 17). The extension shaft 65 has a longitudinal axis 125 (as defined in FIGS. 14 and 17). The striking head portion 70 has a longitudinal axis 120 (as defined in FIG. 16B). In a preferred embodiment of the present invention, the finger engagement longitudinal axis 155 is parallel to or forms an angle within about $\pm 70^\circ$ to the extension shaft longitudinal axis 125. The extension shaft therefore protrudes within a cone having a central axis parallel to the finger engagement portion longitudinal axis. The cone has an included angle of about 140° with an apex coincident with the shaft to finger engagement coupling point 95 (as defined in FIGS. 10, 13A and 13B).

The extension shaft longitudinal axis 125 is also parallel to or forms an angle within about $\pm 30^\circ$ to the striking head longitudinal axis 120. The striking head longitudinal axis therefore protrudes within a cone having a central axis parallel to the extension shaft longitudinal axis. The cone has an included angle of about 60° with an apex coincident with the shaft to striking head coupling point 100 (as defined in FIG. 10).

Finger engagement portions, extension shafts and head portions of the present invention can all be of the same material or these components can be of different materials. For example a finger engagement portion and a head portion of the present invention can be fabricated from a plastic and combined with an extension shaft fabricated from a metal. Finger engagement portions, extension shafts and head portions of the present invention can be formed from numerous materials. These materials include but are not limited to polymers such as polyethylene, polypropylene, polyvinyl chloride, styrenics, polyurethanes, thermoplastic elastomers, nylons, polycarbonate, polyethylene terephthalate, phenolics, thermoset polyesters, silicones, rubber and acetals. Other suitable materials include metals and alloys of gold, silver, tin, nickel, irons, steels, aluminum, coppers and nitinol. Materials used to fabricate components of the present invention can vary in the degree of, for example, rigidity, stiffness, elasticity, toughness, deformability or compliance depending on the configuration and intended purpose of the specific component. Casting, injection molding, compression molding, insert molding, machining, stamping/forming, photo-etching/forming, stereo lithography, wire forming or any other suitable manufacturing method can be used to fabricate devices of the present invention.

EXAMPLE #1

Plastic rings of various sizes and stiffness were procured from a party supply outlet. The selected rings typically had a flat or large oval top portion representing a gem or stone

10

molded onto a finger engagement portion. A typical flat portion of a ring had a surface area of approximately 10 mm (0.4") by 10 mm (0.4") or larger. The rings were typically soft and compliant and could expand to fit tightly onto finger having a diameter of about 15 mm (0.6") to about 20 mm (0.8"). Using a razor, a shallow groove or vee-shaped channel was cut into the top surface of the ring portion that simulated a flat gemstone. The cut channel was about 10 mm (0.4") long, by about 1 mm (0.04") wide and about 1 mm (0.04") deep. This channel was then used to align and mount an extension shaft and head portion onto the finger engagement portion.

A large paper clip having a plastic coated wire with a diameter of about 1.5 mm (0.06") was bent and formed into a rectangular head portion and an extension shaft. The head portion was about 15 mm (0.6") by 8 mm (0.3") and the overall length of the extension shaft and head portion was about 50 mm (2"). The formed wire was then attached to the channel in the top surface of the ring with a 10-minute two part epoxy. After curing the epoxy, the assembly had the general appearance of the device 20 shown in FIG. 10. The modified ring with the attached shaft and head portion was then positioned onto various fingers, finger locations and finger orientations. In an initial outdoor trial, 4 flies and several ants were easily and effectively dissuaded within a 20-minute period.

Although the invention has been described in conjunction with specific embodiments, it is evident that many alterations and variations will be apparent to those skilled in the art in light of the foregoing descriptions and annexed drawings. Accordingly, the invention is intended to embrace all of the alternatives and variations that fall within the spirit and scope of the appended claims.

I claim:

1. A method of deterring an insect, comprising:

- a) supplying an insect deterrent device comprising an extension shaft having a length and first and second opposing end regions, the first shaft end region joined to a finger attachable ring-like structure, the second shaft end region joined to a striking head, the shaft having two cross-sectional perimeters separated by at least about 10 mm with each perimeter having a length that is substantially less than the shaft length, the ring-like structure, extension shaft and striking head each having a longitudinal axis, the ring-like structure longitudinal axis being parallel to or forming an angle within about $\pm 70^\circ$ to the extension shaft longitudinal axis, the extension shaft longitudinal axis being parallel to or forming an angle within about $\pm 30^\circ$ to the striking head longitudinal axis;
- b) releasably attaching the ring-like structure with joined shaft of the deterrent device to a human finger having a distal tip which is not a thumb such that the ring-like structure circumscribes only a single human finger and so that the striking head is positioned distal to the finger distal tip;
- c) forming the finger with the attached deterrent device into a pre-flicked or curled state;
- d) flicking the curled finger to cause the striking head of the deterrent device to strike an insect.

2. The method of claim 1 wherein the striking head has a ball shape.

3. The method of claim 1 wherein the extension shaft with joined striking head is releasably attached to the ring-like structure.

* * * * *